



ShareDiMobiHub

Draft hubs deployment reports Rotterdam

WORK PACKAGE 1 DELIVERABLE 5

August 2024 (City of Rotterdam)

Summary sheet

Project Name	ShareDiMobiHub
Title of the document	Draft hubs deployment reports Rotterdam
Deliverable	D 1.5
Work Package	1
Programme	Interreg NSR
Coordinator	Province of Utrecht
Website	https://www.interregnorthsea.eu/sharedimobihub
Author	Advisor of city of Rotterdam
Status	Public
Dissemination level	Public
Reviewed by	Smart Mobility and Transport Solutions, Mpact and city of Leuven
Submission date	
Starting date	September 2022
Number of months	36

Project partners

Organisation	Abbreviation	Country
Province of Utrecht	ProvU	Netherlands
Capital Region of Denmark	CRD	Denmark
Vestfold and Telemark county	VTFK	Norway
Subpartner: Statens vegvesen	SVV	Norway
Subpartner: Tønsberg kommune	тк	Norway
Subpartner: Porsgrunn municipality	РК	Norway
Subpartner: Skien municipality	SK	Norway
Promotion of Operation Links with Integrated Services	POLIS	Belgium
City of Amsterdam	AMS	Netherlands
City of Leuven	LEU	Belgium
University of Antwerp	UAntw	Belgium
Transport Authority for the Amsterdam Region	VRA	Netherlands
Mpact	Mpact	Belgium
Autodelen.net	Auto	Belgium
City of Rotterdam	ROT	Netherlands
Hamburg University of Applied Sciences	HAW	Germany
University of Applied Sciences Utrecht	HU	Netherlands

Document history

Version	Date	Organisation	Main area of changes	Comments
0.1	July 2024	City of Rotterdam		
1.0	August 2024	City of Rotterdam		

Table of Contents

Summary sheet	.2
Project partners	.3
Document history	.4
. Introduction	.6
2. Hub Deployment Process	.6
2.1 Site Preparation	.7
2.1.1 For sidewalk-based hubs	.7
2.1.2 For parking space-based hubs	.7
2.2 Digital Integration	.8
2.3 Monitoring and Evaluation	.8
8. Best Practics	.8
. Conclusion	.9
he ShareDiMobiHub Consortium	10

1. Introduction

This document outlines the process for deploying shared mobility hubs in Rotterdam as part of the ShareDiMobiHub projecit provides a step-by-step guide for preparing locations, including obtaining permits, modifying existing infrastructure, and implementing best practices. The goal is to create efficient and user-friendly mobility hubs that encourage the use of shared transportation options.

2. Hub Deployment Process

In Rotterdam there are different types of hubs. A shared mobility hub in this document is a mobility hub for shared-(cargo)bikes, with or without electric assistance, and mopeds. This shared mobility hub is characterized by white markings on the ground and a green hub sign in the national 'Mijksenaar hub' style. An example of this shared mobility hub is pictured below.



Figure 1: Example of a sidewalk-based hub

2.1 Site Preparation

Before deploying a mobility hub, the following steps are taken to prepare the location:

2.1.1 For sidewalk-based hubs

- 1. Assess the need for removing or relocating existing street furniture (e.g., bike racks, poles).
- 2. If removal/relocation is necessary:
 - a. Consult with the relevant people within the municipal department.
 - b. Upon approval, the department responsible for public space construction implements the changes.
- 3. If no changes are needed or once changes are completed:
 - a. Commission an external organization to apply white lines on the sidewalk, marking the hub area. This is chosen because it's faster, environmentally friendly, and easier to remove when the hub is not performing well.
 - b. Install a standardized HUB pole next to the parking spaces.

2.1.2 For parking space-based hubs

- 1. Evaluate the parking space configuration. This is based on parking pressure counting. When this is over 80% it is not possible to place a shared mobility hub.
- 2. If there are not two 'vertical' parking spaces with 'ears' on the sides, or in other words, in the situation a parking space is located directly besides the hub:
 - a. Order and install a planter on the third parking space to prevent vehicles from falling against cars, Figure 3.
- 3. If the location is sensitive to parking space removal, inform nearby residents via letter. This depends on the situation, for example the entire street or within a radius of 200 meters.

Below the different options are visualized.




Figure 2: Hub on parking space with two 'ears'

Figure 3: Hub on parking space with one 'ear' and a planter

- 4. Once the space is prepared:
 - a. Apply white lines to mark the hub area.
 - b. Install a standardized HUB pole next to the parking spaces.

2.2 Digital Integration

After physical installation

- 1. Add the hub to the "dashboard deelmobiliteit" (shared mobility dashboard).
- 2. Create a 200m no-parking zone around the hub in the dashboard.
- 3. Share hub and no-parking zone information with shared mobility providers for integration into their apps. A KML-file of the hub is downloaded from the shared mobility dashboard. This KML-file will be sent to the different shared (cargo)bikes and moped providers via E-mail.

2.3 Monitoring and Evaluation

- 1. Use the shared mobility dashboard and a custom PowerBI dashboard to monitor:
 - Number of rentals from each hub
 - Number of vehicles present in different hubs
- 2. Use this data to inform decisions on:
 - Altering hub size
 - Placing new hubs in surrounding areas
 - Removing underperforming hubs

3. Best Practics

Based on Rotterdam's experience, the following best practices are recommended for efficient hub deployment:

Standardization: Use consistent branding and signage (e.g., HUB poles) to increase visibility and user recognition.

Internal communication: Create a clear oversight of the different stakeholder involved in the process of placing shared mobility hubs. Involve these internal stakeholders in the decision-making process of the location of the hubs. These include landscape architects, traffic engineers, neighbourhood representatives and potentially colleagues from other clusters. (for example bicycle parking or street execution). To ensure an ongoing process clearly depict everyone's roll and who needs to be involved in which step. In this way it is possible to ensure placement of hubs in a relatively short time. The exact time depends per location.

Flexible Design: Opt for easily removable markings (e.g., glued white lines) to allow for quick adjustments if a hub underperforms.

Digital Integration: Ensure seamless integration with mobility apps and dashboards to facilitate user adoption and data-driven decision-making.

Community Engagement: Inform and involve local residents, especially when removing parking spaces, to build support and address concerns.

Multi-stakeholder Collaboration: Work closely with shared mobility providers, municipal departments, and local stakeholders throughout the process.

Adaptive Management: Continuously monitor hub performance and be prepared to make adjustments based on usage data and community feedback.

Environmental Considerations: Choose eco-friendly materials and methods where possible, such as using glued lines instead of paint.

4. Conclusion

The deployment of shared mobility hubs requires careful planning, stakeholder engagement, and ongoing monitoring. By following these procedures and best practices, cities can create effective hubs that encourage the use of shared mobility options, reduce street clutter, and improve overall urban mobility.

The ShareDiMobiHub Consortium

The consortium of ShareDiMobiHub consists of 13 partners and 4 subpartners with multidisciplinary and complementary competencies. This includes European cities and regions, universities, network partners and transport operators.



For further information please visit https://www.interregnorthsea.eu/sharedimobihub

The sole responsibility for the content of this document lies with the authors. It does not necessarily reflect the opinion of the European Union. Neither Interreg Northsearegion nor the European Commission are responsible for any use that may be made of the information contained therein.